



Quick Service Restaurants / Food Court Restaurants



Table Service Restaurants



Liquor Stores / Retail Stores



Coffee Stores

## POS Touch Screen Terminal



### Powerful All-in-One Terminal With Celeron Dual Core Processor

The IT-5000 is ideally suited for the most demanding retail and hospitality applications.

- Intel® E1500 Celeron Dual Core 2.2 GHz Processor
- 15" LCD With 5-Wire Resistive Touch
- 10/100/1000 Base-T Giga Lan
- Spill Resistant Housing
- Concealed Power Switch And Control Panel
- Built In Power Supply
- Standard Integrated MCR
- Optional Integrated Customer Displays



# IT-5000 Touch Screen Terminal



Standard Triple Track MCR



Optional Integrated 15" Rear LCD Customer Display



Optional Integrated VFD Customer Display



0° ~ 90° Tilt Angle

## Options and Upgrades

Configure your system with these easy to add options:

- Integrated VFD Customer Display – 2 Lines x 20 Characters
- Integrated 15" LCD Customer Display
- Integrated Speakers
- WINDOWS XP Pro / XP Pro Embedded / WePOS / POSReady 2009 Operating Systems
- Wall Mount Brackets With Standard VESA Configuration

## Applications

The attractive, powerful IT-5000 is ideal for demanding applications including table service, retail scanning and many more like these:

- Airline Counters
- Automotive
- Convenience Stores
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food/Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- Kitchen Video
- Medical
- Message Stations
- Point of Sale
- Quick Service Restaurant
- Rental Car Counters
- Retail Scanning
- Self Service
- Streaming Video
- Table Service Restaurant
- Training
- Unattended Workstations

## Connectivity

- A Fan
- B Hard Disk Drive \*
- C Power In
- D COM3 (Powered)
- E Line-Out
- F Mic-In
- G Line-In
- H USB (2)
- I LAN
- J COM5
- K DVI (For Rear LCD)
- L COM4 (Powered)
- M Parallel
- N USB (2)
- O COM1
- P PS/2

\* Easy Access To The Hard Disk Drive Without Opening The Cabinet

## Specifications

<b>Processor:</b>	Intel E1500 Celeron Dual Core 2.2 GHz
<b>FSB:</b>	533 MHz
<b>Socket Type:</b>	BGA
<b>Display LCD:</b>	15" XGA TFT LCD
<b>Resolution:</b>	1024 x 768
<b>Maximum Brightness:</b>	250 cd/m <sup>2</sup>
<b>Integrated Speakers:</b>	Optional Integrated Speakers
<b>Chipset:</b>	Intel G41 Express Chipset
<b>Touch Panel:</b>	5-Wire Resistive Touch
<b>MCR:</b>	Integrated Triple Track MCR
<b>Hard Drive:</b>	Integrated 2.5" 160G
<b>RAM Memory:</b>	Two 240-Pin DDR3 SDRAM Sockets Support Up To 4G
<b>Video Memory:</b>	Intel GMA x 4500 Onboard Graphics System
<b>Compact Flash Disk:</b>	Not Applicable
<b>Mini-PCIe:</b>	One Slot on Motherboard
<b>Serial Ports:</b>	COM1, COM5 = DB9 COM3, COM4 = DB9 With Pin 9 0V/5V/12V (Selectable)
<b>Parallel Port:</b>	One D25
<b>USB Ports:</b>	Four USB 2.0
<b>Cash Drawer Port:</b>	Not Applicable
<b>Keyboard / Mouse Port:</b>	One PS/2 Mini-DIN
<b>LAN Port:</b>	One RJ45 Gigabit 10/100/1000 Base-T
<b>DVI Port:</b>	One For Rear LCD
<b>Audio Port:</b>	One Line-Out
<b>Mic Port:</b>	One Mic-In
<b>Power Supply:</b>	150W Internal Power Supply 100-240V 50-60Hz
<b>Current / Power Usage:</b>	1.1A / 127W
<b>Operating Temperature:</b>	32° F to 95° F (0° C to 35° C) Non-Condensing
<b>Compatible O/S:</b>	XP Pro / XP Pro Embedded / POSReady 2009 / WePOS / VISTA / Windows® 2000 / Windows® 7 / Linux®
<b>Dimensions – Base:</b>	11-1/4" x 8-1/4" x 8-5/8"
<b>Overall:</b>	15"W x 12-1/2"H x 8-1/2"D
<b>Shipping Carton:</b>	20" x 18" x 11-1/2"
<b>Weight – Product:</b>	14.14 lbs.
<b>Shipping:</b>	19 lbs.
<b>Safety and EMI:</b>	FCC, RoHS

